<u>HS900W KIT – COMBINATION TOPPER HEDGER SKIRTER</u> SPECIFICATION SHEET

SP	ECIFICATIONS:					
	CUTTING STAR DIAMETER9' (274 CM)					
	MINIMUM FLAT SKIRTING HEIGHT2' (61 CM)					
	MAXIMUM HEDGING HEIGHT23' 9" (724 CM)					
	MAXIMUM FLAT TOPPING HEIGHT14' (427 CM)					
	MAXIMUM REACH FROM CENTER (FLAT TOPPING)13' (397 CM)					
	TRANSPORT HEIGHT					
	MACHINE WEIGHT (DRY KIT ONLY)5800 LBS (2630 KG)					
	SAW BLADES3 - 24" DIAMETER, PROPRIETARY SAW BLADES					
NO	TE: ALL DIMENSIONS ARE APPROXIMATE. ACTUAL DIMENSIONS WILL DEPEND ON THE TRACTOR USED FOR MOUNTING					
Thi	OPELLING UNIT: s model is supplied as a KIT to be mounted on the customer's tractor. Basic tractor model should have approximately - 90 HP with a 4 cylinder engine.					
IN	CLUDED OPTIONS:					
	Steel operators cab including a front windshield. Rotation speed control valve.					
HY	TDRAULIC SYSTEM:					
	Saw blade rotation circuit — COMMERCIAL gear type pump. Cutting star rotation circuit — COMMERCIAL gear type pump. Control circuit — tractor internal pump operating: Tower lift cylinder Main arm cylinder Cutting star cylinder.					

SAFETY:

In the design, components selection, and manufacturing, as well as in the servicing and operating instructions, much thought has been given to provide a machine with high productivity, low maintenance, long life, and above all, operator safety.

T	TT	E	D	A	T	II	D	\mathbf{r}	
L	11	. L.	N.	А	1	U	Л	Ŀ	÷

Each unit is supplied with full documentation for all systems. This includes a "General Safety and Operations Manual" and a "Spare Parts and Specifications Manual".

FI	NISH:							
	Machine parts are sand blasted, primed and painted.							
	☐ Machine bolts are zinc plated, grade 5.							
	T (, ,) , ,							
	The machine is assembled and each system is fully tested. Final adjustments are made to ensure the machine is ready for							
	use.							
	<u>Note</u> : Some parts are disassembled for shipping.							
	RICE: ease inquire for pricing.							
OF	PTIONS: Brush guard - Wide guard u	nder the length of tractor						
SA	LE CONDITIONS							
	PRICES	F.O.B., TOL Incorporated						
	DELIVERY	According to availability						
	TERMS	20% deposit required to confirm an order.						
		Balance due on delivery.						
	ACKING: ur "KITS" in 20' container.							
NO	OTES: As our policy is of continu	nous improvement, we reserve the right to change specifications and design without prior						
notice.								