

**TH1000SK KIT – COMBINATION TOPPER HEDGER SKIRTER**  
**SPECIFICATION SHEET**

**SPECIFICATIONS:**

- CUTTING STAR DIAMETER.....11’ 2” (340 CM)**
- SKIRTING - REACH FROM THE CENTER.....13’ 1” (398 CM) at 40°**
- MINIMUM FLAT SKIRTING HEIGHT .....2’ 6” (76 CM)**
- MAXIMUM HEDGING HEIGHT.....28’ (853 CM)**
- MAXIMUM FLAT TOPPING HEIGHT.....17’ 6” (533 CM)**
- MAXIMUM REACH FROM CENTER (FLAT TOPPING).....14’ 2” (432 CM)**
- TRANSPORT HEIGHT.....9’ 9” (297 CM)**
- MACHINE WEIGHT (DRY KIT ONLY).....6820 LBS (3100 KG)**
- SAW BLADES.....4 - 24” DIAMETER, PROPRIETARY SAW BLADES**

NOTE: ALL DIMENSIONS ARE APPROXIMATE. ACTUAL DIMENSIONS WILL DEPEND ON THE TRACTOR USED FOR MOUNTING

**PROPELLING UNIT:**

This model is supplied as a **KIT** to be mounted on the customer’s tractor. Basic tractor model should have approximately 70 - 90 HP with a 4 cylinder engine.

**INCLUDED OPTIONS:**

- Steel operators cab including a front windshield.
- Rotation speed control valve.

**HYDRAULIC SYSTEM:**

- Saw blade rotation circuit – **COMMERCIAL** gear type pump.
- Cutting star rotation circuit – **COMMERCIAL** gear type pump.
- Control circuit – tractor internal pump operating:
  - Tower lift cylinder
  - Horizontal to vertical cylinder
  - Cutting star swing cylinder.

**SAFETY:**

In the design, components selection, and manufacturing, as well as in the servicing and operating instructions, much thought has been given to provide a machine with high productivity, low maintenance, long life, and above all, operator safety.

**LITERATURE:**

Each unit is supplied with full documentation for all systems. This includes a “General Safety and Operations Manual” and a “Spare Parts and Specifications Manual”.

**FINISH:**

- Machine parts are sand blasted, primed and painted.
- Machine bolts are zinc plated, grade 5.
- Saw blade propelling and rotation parts (shafts, washers, etc.) are zinc plated.
- The machine is assembled and each system is fully tested. Final adjustments are made to ensure the machine is ready for use.

**Note:** Some parts are disassembled for shipping.

**PRICE:**

Please inquire for pricing.

**OPTIONS:**

- Brush guard - Wide guard under the length of tractor

**SALE CONDITIONS**

- |  |   |
|--|---|
| <input type="checkbox"/> <b>PRICES</b>   | F.O.B., TOL Incorporated  |
| <input type="checkbox"/> <b>DELIVERY</b> | According to availability   |
| <input type="checkbox"/> <b>TERMS</b>    | 20% deposit required to confirm an order.<br>Balance due on delivery. |

**PACKING:**

Four “KITS” in 20’ container.

**NOTES:**

- As our policy is of continuous improvement, we reserve the right to change specifications and design without prior notice.